

500W, Encapsulated AC/DC Power Supply for Heavy Duty Applications POL 319 Series

- Extremely rugged field-proven design
- Full encapsulation
- Single output
- Full electronic protection
- High reliability
- Conduction cooling

**Not for new design.
Please contact factory
for alternative design.**



The POL 319 Series compact AC/DC power supply which uses half-bridge technology to convert a 115 or 230Vac input to the required voltage. Designed for operation in very harsh environments, the unit is entirely potted with a thermally conductive MIL-spec silicon rubber compound to increase resistance against humidity, moisture, shock, vibration, dust and insects. It is conduction cooled via a base plate. The POL 319 was designed for continuous operation in a -40°C to a +70°C temperature range when installed on an appropriate heatsinking surface. This converter features full electronic protection, high efficiency and low output noise. The use of components with many years of established reliability and generous headroom contributes to an MTBF exceeding 180,000 hours at 45°C. The POL 319 is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Input Voltage / Current

115/230VAC +/- 15%
47 - 63Hz, selection by jumper
Input current:
5A max at 230VAC input;
10A at 115VAC input
The unit also accepts a 230Vdc to 370Vdc input range
Consult factory for other voltages

Input Protection

Inrush current limiting
Varistor
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Input Isolation

2250VDC input to chassis
4300VDC input to output,
8mm spacing
500VDC output to chassis

Standards

Designed to meet EN60950 and related corresponding UL and CSA standards

EMI

EN 55022 Class A as a minimum

Switching Frequency

55KHz +/- 3KHz

Hold Up Time

Min 5ms at nominal input for 5% drop of output voltage

Output Voltage/Current

12V/40A, 24V/20A or 48V/10A
Contact factory for other configurations
Output is floating, either terminal can be grounded

Redundancy Diode

None

Line/Load Regulation

+/- 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple / Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHZ BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
Thermal shutdown in case of insufficient cooling (self resetting)
Current Limit: typically 110% of nominal

Output Overvoltage Protection

Second regulator loop
OVP setting: typically 120% of nominal

Efficiency

80% at full load

Operating Temperature Range

-40°C to +70°C cold plate temperature for full specification

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction via base plate to customer heatsink or chassis

Environmental Protection

Full encapsulation

Shock/Vibration

Designed to meet requirements of IEC 61373 Cat 1 A&B and Cat 2 as a minimum

MTBF

180,000 hours at 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None

Alarm Output

None on standard version

Dimensions (W x H x L)

152 x 79 x 353 mm
6" x 3.1" x 13.9" including terminal block and flanges

Weight

5.6 kg (12.5 lbs)

Connections

AC input: 3-pole barrier type terminal block with 3/8" spacing
Output: 1/4"-20 NC studs
Optional alarm: 4 pole Phoenix connector.

RoHS Compliance

(Directive 2002/95/EC)
Fully compliant

Warranty

Two years subject to application within good engineering practice



European Stocking Distributor

Phone: +41 44 730 33 53

Email: sales@hvps-condatas.com / www.hvps-condatas.com
Rietbachstrasse 7, 8952 Schlieren (ZH), Switzerland