



# SP7220, 10W, Prop. SPECIFICATION SHEET



**Standard Model Number : SP7220**

**RoHs Model Number : SP7220/Y**

## ELECTRICAL SPECIFICATIONS

*Standard Model is NOT RoHs Compliant*

Input Voltage .....	0 - 12Vdc	No Load Input Current .....	<200mA
Output Voltage .....	0 to + or - 200Vdc	Full Load Input Current .....	<1.1A
Output Current .....	50 mA	Input Filter .....	LC Input Filter
Voltage Accuracy .....	+/- 5%	Efficiency .....	> 75%
Line Regulation .....	Proportional	Short Circuit Protection .....	Continuous
Load Regulation .....	+/- 10%	Switching Frequency .....	60 kHz
Output Ripple .....	< 0.5% P-P	Output Isolation .....	6500 Vdc
Start-up Voltage .....	< 0.7Vdc	Input / Output Capacitance .....	< 30pF
		<b>Guaranteed Start-up Load (6Vdc IN) .....</b>	<b>10uF &amp; &gt;5mA CCL</b>

## GENERAL SPECIFICATIONS



Temp. Stability .....	+/- 0.05%/°C	EMI/RFI .....	Six-Sided Shield
Temp. (Operating , Case) .....	-20 to +85°C	Derating .....	None
Temp. (Storage) .....	-55 to +100°C	Cooling .....	Free-Air Convection
Humidity .....	0 to 95% (Non-Condensing)		

## PHYSICAL SPECIFICATIONS

Dimensions .....	1.7 x 2.6 x 0.85 inches	Case Material .....	Black Coated Metal
Weight .....	4.1 Oz		(With Non-Conductive Base Plate)



# SP7220, 10W, Prop. SPECIFICATION SHEET



*Dimensions are in Inches  
[Metric equivalents in brackets]*



"The best high voltage design solution"

## SP7220 SPECIFICATION SHEET

### APPLICATION NOTES

#### CLEANING AGENTS

In order to avoid possible damage, any penetration of cleaning fluids must be prevented, since the power supplies are not hermetically sealed.

#### NUCLEAR AND MEDICAL APPLICATIONS

American Power Design products are not designed, intended for use in, or authorized for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems without the express written consent of American Power Design, Inc.

#### SAFETY REQUIREMENTS

The converters are designed to meet North American and International safety regulatory requirements per UL 60950-1/CSA 22.2 No. 60950-1-07 Second Edition, IEC 60950-1:2005, and EN 60950-1:2006. Basic Insulation is provided between input and output. To comply with safety agencies requirements, an input line fuse (2A SB) must be used external to the converter.

If one input fuse is used for a group of modules, the maximum fuse rating should not exceed 20A.

#### WARRANTY

All products manufactured by American Power Design, Inc. (APD) are warranted to be free of defects due to material or workmanship for a period of one year from date of shipment. At our option, APD will repair or replace any non-conforming product.

APD expressly disclaims any liability for consequential or incidental damages resulting from the use or misuse of its products by the purchaser or others.

This warranty is in lieu of all warranties expressed or implied, including the warranties of merchantability. No other warranties, obligations, or liabilities are expressed or implied.

All products being returned for repair require a return material authorization(RMA) assigned by APD prior to return shipment.