




"The best high voltage design solution"

SP7261, 50W Reg. SPECIFICATION SHEET



P/N will be SP7261/Y

Standard Model Number : SP7261

RoHs Model Number : SP7261/Y

ELECTRICAL SPECIFICATIONS

Standard Model is NOT RoHs Compliant

Ultra Wide Input Ranges

Input Voltage 20Vdc to 120Vdc
 Output Voltage #1 + or - 120Vdc
 Output Current #1 125mA
 Output Voltage #2 + or - 120Vdc
 Output Current #2 125mA
 Voltage Accuracy < 1%
 Line Regulation < 0.2%
 Load Regulation < 0.3%

Output Ripple < 0.4 % P-P
 Input Filter Pi Network
 Efficiency 84% (typ.)
 Short Circuit Protection Continuous
 Switching Frequency 120 kHz

Isolation (Input-Output(1)-Output(2)-Case) 1000 Vdc

Independently Isolated Outputs

Input / Output Capacitance < 100pF

UL Certified Encapsulant Meets 94V-0 Flammability

Remote On/Off Control

GENERAL SPECIFICATIONS

Temp. Stability +/- 0.02%/°C
 Temp. (Operating , Case) -45 to +85°C
 Temp. (Storage) -55 to +100°C
 Humidity 20 to 85% (Non-Condensing)

Logic Shutdown Logic 0 (on)
 Thermal Shock Limit 1°C / 10 Seconds

EMI/RFI Six Sided Shield

Derating None
 Cooling Free-Air Convection

PHYSICAL SPECIFICATIONS

Dimensions 2.57 x 4.57 x 0.84 inches
 Weight 12.7 Oz

Case Material Black Coated Metal
 (With Non-Conductive Base Plate)



"The best high voltage design solution"

SP7261, 50W Reg. SPECIFICATION SHEET

APPLICATION NOTES

CLEANING AGENTS

In order to avoid possible damage, any penetration of cleaning fluids must be prevented, since the power supplies are not hermetically sealed.

NUCLEAR AND MEDICAL APPLICATIONS

American Power Design products are not designed, intended for use in, or authorized for use as critical components in life support systems, equipment used in hazardous environments, or nuclear control systems without the express written consent of American Power Design, Inc.

SAFETY REQUIREMENTS

The converters are designed to meet North American and International safety regulatory requirements per UL 60950-1/CSA 22.2 No. 60950-1-07 Second Edition, IEC 60950-1:2005, and EN 60950-1:2006. Basic Insulation is provided between input and output. To comply with safety agencies requirements, an input line fuse (3.5A SB) must be used external to the converter.

If one input fuse is used for a group of modules, the maximum fuse rating should not exceed 20A.

WARRANTY

All products manufactured by American Power Design, Inc. (APD) are warranted to be free of defects due to material or workmanship for a period of one year from date of shipment. At our option, APD will repair or replace any non-conforming product.

APD expressly disclaims any liability for consequential or incidental damages resulting from the use or misuse of its products by the purchaser or others.

This warranty is in lieu of all warranties expressed or implied, including the warranties of merchantability. No other warranties, obligations, or liabilities are expressed or implied.

All products being returned for repair require a return material authorization(RMA) assigned by APD prior to return shipment.