180W, SINGLE OUTPUT POWER SUPPLY EOL90 SERIES

- Compact size 10.0" x 4.43" x 2.25"
- Single regulated and adjustable output
- 180W output with conduction cooling
- Full electronic protection
- Telecom quality
- Field-proven design topology
- Also available as plug-in module
- N+1 redundancy available



The EOL90 Series of AC/DC converters uses high frequency dual FET forward topology to generate 180W of output power. Virtually any DC output is possible with short delivery times. This low profile design features low component count and high efficiency. The use of high quality components and rigorous quality control results in an MTBF exceeding 100,000 hours at 45°C.

SPECIFICATIONS

Input Voltage

115/230VAC +/- 15% 47 - 63Hz Auto-ranging available

Input Protection

Thermal Fuse Inrush current limiting

Input Isolation

2250VDC input to chassis 4300VDC input to output, 8mm spacing 500VDC output to chassis

Full compliance to IEC950, CSA C22.2 No. 950 and UL 1950 Please contact factory for approval status for the requested input/output configuration

EMI

Meets EN 55022 Class A

Output Voltages/Currents

12V/15A; 24V/7.5A, 48V/3.75A, standard Consult factory for other voltages

Line/Load Regulation

+/-1% combined

Output Over-voltage Protection

Double regulator loop

Overload Protection

Current limiting with short circuit protection Self-resetting thermostat for thermal protection

Efficiency

Min 80% at full load

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20HZ BW)

Hold Up Time

Minimum 10ms at full load for 5% drop of output voltage

Operating Temperature

0 to +50°C, unit must be mounted on a heat sinking surface Extended temperature range available

Temperature Drift

0.03% per °C over operating temperature range

Dimensions

'F'2 Package: 10" x 4.43" x 2.25"

Connections:

Screw type terminal block For other connectors please consult factory

Warranty

Twelve months subject to application within good engineering practice

