

30W, Encapsulated DC/DC Converter for Railway, Mobile and Industrial Applications

RWY 30-P30 Series

- Rugged, field-proven design
- Full encapsulation
- Wide temperature range
- Full electronic protection
- EN 50155 input ranges



This fully encapsulated, railway quality power converter utilizes field-proven technology to generate the required output power. It is a mature design with a track record in numerous applications. The unit is entirely potted with a thermally conductive MIL-grade silicon rubber compound which provides protection from moisture and other contaminants, as well as immunity to shock and vibration. Cooling is by conduction via a base plate to a heatsinking surface. Full electronic protection, low component count, large design headroom and the exclusive use of components with established reliability contribute to a high MTBF. The unit meets the requirements of EN50155 for electronic equipment used on railway rolling stock. It is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Standard Input Voltages

24Vdc (14.4 – 34V)
36Vdc (22 – 51V)
48Vdc (29 – 67V)
72Vdc (43 – 101V)
96Vdc (58 – 135V)
110Vdc (66 – 154V)
Other inputs upon request

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than specified
minimum input will not damage
unit

Isolation

1500Vdc input to chassis
3000Vdc input to output
1500Vdc output to chassis

Standards

Designed to meet EN60950-1 and
EN50155

Immunity

Meets criteria of EN50155 and
EN50121-3-2 according to the
following standards:
EN 61000-4-2 (ESD)
EN61000-4-3 (RF Immunity)
EN61000-4-4 (Fast Transients)
EN50155 (Surge)
EN61000-4-6 (Conducted Imm.)
EN50155 (Voltage Variations)

EMI

EN50121-3-2

Switching Frequency

100kHz \pm 5kHz

Output Voltage

Any voltage in the 5V to 110V range
Output is floating, either terminal
can be grounded
Other outputs upon request

Redundancy Diode

None

Line/Load Regulation

\pm 1% combined from zero load
to full load

Dynamic Response

Max 5% voltage deviation for 10%
to 50% load step, with better than
1msec recovery time

Output Ripple/Noise

Less than 1% peak-to-peak or
0.2% RMS of the output voltage
(20MHz BW)

Output Overload Protection

Rectangular current limiting with
hiccup type short-circuit
protection

Output Overvoltage Protection

Transzorb installed across the
output

Efficiency

80 to 90% at full load depending
on input/output configuration

Operating Temperature Range

-40 to +70°C cold-plate
temperature for full specification

Temperature Drift

0.03% per °C over operating
temperature range

Cooling

Conduction cooling via base plate
to customer chassis or heat-sink

Environmental Protection

Full encapsulation with thermally
conductive silicon potting
compound with UL94V-0
flammability rating
Meets environmental criteria as
requested in MIL-810 C, D

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing
Contact factory for higher rating

MTBF

150,000 hours @ 45 °C
Demonstrated MTBF is
significantly higher

Indicators

None
Optional 'ON' LED adapter available

Control Input

None

Alarm Output

None

Package/Dimensions (W x H x L)

P30: 56 x 56 x 147mm
(2.2" x 2.2" x 5.8")
Includes terminal block and flanges.
The case has clear alodine finish
according to MIL-C-5541E Class 3
Mounting holes are clear

Weight

0.5 kg (1.1 lb)

Connections

5-pole barrier-type terminal block
with 3/8" spacing
Cover can be provided upon
request

RoHS Compliance

Compliant

Warranty

Two years subject to application
within good engineering practice.

Terminal Block Pin-out

OUTPUT		GND	INPUT	
+	-		+	-
1	2	3	4	5



European Stocking Distributor

Phone: +41 44 730 33 53

Email: sales@hvps-condatas.com / www.hvps-condatas.com

Rietbachstrasse 7, 8952 Schlieren (ZH), Switzerland